

sewoo

3-Inch Direct Thermal POS Printer

SLK-TL100II




- Fast printing speed(200mm/sec)
- Maximize productivity with Compact and Sleek design
- The simplest and efficient design for environments with limited space
- Reduce power consumption and cost through energy star certification
- High reliability mechanism: 1.5 Million of Cutter life and 160km of TPH Life



Barcode



Durable



Paper
Width



Light
Weight



Easy
Loading



Fast Speed



Compact
Design



Easy
Maintenance

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 200mm/sec(7.8ips)

Print Width

Up to 72mm(2.8")

Resolution

180 dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper end, Paper low ,

Cover open

Optional: Black mark

Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 2.0 Million cuts

Drawer port

2 Circuit(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

136 x 165 x 111mm

(5.35" x 6.49" x 4.37")

Weight

1.0Kg(2.2lb)



INTERFACES

Standard

USB(B type)+Serial(RS-232C_9pin)

Built-in

Optional

Bluetooth Smart Ready

(Bluetooth4.2+BLE)



CERTIFICATIONS

CB, CE, FCC, KC



OPERATING CHARACTERISTICS

Operating Temperature

41 ~ 104°F(5 ~ 40°C)

Operating Humidity

10 ~ 90%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Media Width

79mm ± 0.5mm(3.11")

Media Core Diameter

12.5mm ± 0.5mm(0.4")

Media Roll Diameter

Max. ø 83mm(3.2")

Thickness

0.06~0.09mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Windows CE & Mobile Driver (CE 4.2 ~,

Mobile 5.0 ~), Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK, Windows SDK,

Windows CE SDK, Linux SDK



BARCODES

1D

EAN-8, EAN-13, Code 39, Code 93,

Code 128, ITF, UPC-A, UPC-E, Codabar

2D

PDF 417, QR code, DATA MATRIX



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Chinese/Korean/Japanese: 21cpl

Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Optional

Melody box, 24V Buzzer,

Paper Guide

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA_Sales@miniprnter.com

