

sewoo

3-Inch POS Printer

SLK-TS100




- High Performance Easy Maintenance
- Ergonomic Design Entry-level Printer
- Easy maintenance with Jam release lever
- Simple and easy replacement of components including head, motor, cutter, PCB, etc
- Easy maintenance for paper jam
- Ideal for top exit printing with wall mount
- High speed printing at 8.6ips (220mm/sec)



Barcode



Durable



Paper Width



Easy Loading



Fast Speed



Compact Design



Easy Maintenance

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
220mm/sec

Print width
2.83"
(72mm, adjustable by commands)

Resolution
203 dpi

Power
Power type : External SMPS
AC : 110~220Vac 50/60Hz
DC : 24Vdc / 2.5A

Sensor
Paper end, Cover open

Reliability
TPH life : 100km
MCBF : 80 Million lines
Cutter life : 1.5 Million cuts

Drawer port
circuit (24V, Max. 1A)

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
5.59" x 7.28" x 5.35"
(142 x 185 x 136mm)

Weight
2.25b(1.02Kg)

INTERFACES

1. USB+SEIRAL(RS-232C_9pin)+RJ45 serial+Ethernet Built-in
2. USB+SEIRAL(RS-232C_9pin)+RJ45 serial (korea standard)

CERTIFICATIONS

CE, FCC, KC,ENERGY STAR, ROHS

OPERATING CHARACTERISTICS

Operating Temperature
32 ~ 113°F(0 ~ 45°C)

Operating Humidity
10 ~ 80RH%

Storage Temperature
14 ~ 140°F(-10 ~ 60°C)

Storage Humidity
10 ~ 90RH%

MEDIA CHARACTERISTICS

Media Type
Thermal receipt paper

Media Width
79.5±0.5mm

Media Core Diameter
0.49~0.5"(12.5mm ± 0.5mm)

Media Roll Diameter
3.1"(Max. ø 80mm)

Thickness
0.06~0.08mm

SOFTWARE

Emulations
ESC/POS Command compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Linux Driver, Mac Driver, OPOS Driver,
JavaPOS Driver

SDK
Android(6.0 ~) SDK, Windows SDK

BARCODES

1D
EAN-8, EAN-13, Code 39,
Code 93, Code 128, ITF,
UPC-A, UPC-E, Codabar

2D
PDF 417, QR code

CHARACTERISTICS / FONTS / GRAPHICS

Character Type
Font A(12x24), Font B(9x17),
Chinese(Traditional/Simplified, 24x24),
Korean(24x24), Japanese(24x24)

Characters per line (CPL)
· 180dpi
Font A(12x24) : 42cpl,
Font B(9x17) : 59cpl,
· 203dpi
Font A(12x24) : 48,
Font B(9x17) : 64cpl
Chinese/Korean/Japanese: 24cpl

Character set
95 Alphanumeric,
16 International,
128 x 18 Graphic

ACCESSORIES

- Built in melody standard**
1. SLK-TS100E(USB + Serial + Ethernet)
: Built in melody
 2. Korea standard
(USB+SEIRAL(RS-232C_9pin)+RJ45 serial)
: Built in melody

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_Sales@miniprinter.com

México

Cauhtémoc, Mexico D.F.
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_Sales@miniprinter.com

