

sewoo

Robust and durable label mobile printers

LK-P30II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Rugged design for Drop resistant
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged Design



Drop Resistant



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
100mm/sec

Print Width
72mm, 576 Dots/line

Resolution
203 dpi (8dots/mm, 0.125 Pitch)

Memory
16MB(Max.32MB) Flash,
8MB SDRAM

Battery Voltage / Capacity
7.4V 2600mAh Li-ion,
7.2V 3350mAh Li-ion

Battery Charge Time
3.3Hrs (2600mAh),
4Hrs (3350mAh)

Standby Time
100Hrs (2600mAh),
90Hrs (3350mAh)

Sensor
Paper end, Black mark,
Cover open, Gap

Reliability
TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x L x D)
4.72"×5.98"×2.75"
(120×152×70mm)

Weight
640g (with Battery)



INTERFACES

Standard
USB, Serial(RS-232C)

Option
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE)



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, M,
UKCA, BCS, CB



OPERATING CHARACTERISTICS

Operating Temperature
-10 ~ 50°C

Operating Humidity
10 ~ 80%

Storage Temperature
-20 ~ 60°C

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP42, IP54(with case) certified

Drop Rating
1.2m(set only), 1.8m(with case)



BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
UPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations
ESC/POS, CPCL, ZPL

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS
Driver, iOS SDK, Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type
Thermal Receipt/Label

Media Width
25 ~ 80mm

Media Core Diameter
12.5mm ± 0.5mm

Media Roll Diameter
Max. Ø 56mm

Thickness
0.06 ~ 0.16mm



FONTS / GRAPHICS

Character Type
FontA(12x24), FontB(9x17),
Font0/1/2/4/5/6/7, TTF Font0, FontA~H,
FontGS, Font1~8, Asian Font(KOR, JPN,
CHN_GB2312, CHN_BIG5), Resident TTF,
Downloadable TTF, Downloadable Bitmap

Characters per Line (CPL)
Font A(12x24): 48 columns,
Font B(9x17): 64 columns

Character Set
Alpha numeric character : 95
Expanded graphic :
128*18 page(1 space page)
International character : 14



ACCESSORIES

Standard
USB Cable, Battery Pack, Serial Cable
Thermal Roll Paper, Belt Buckle,
Battery Charger (8.4V)

Optional
Battery Cradle (P30), Vehicle Charger,
Leather Case, Shoulder Trap, RTC
4 Bay Cradle

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com

