

sewoo

Super-rugged & high-portability with LCD display

LK-P43II



- Fast Print Speed
- Excellent Compatibility
- Quick and easy to support peel mode
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Rugged Design



Drop Resistant



Easy Loading



100
mm/sec

Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



Non Peeler

NON PEELER

Peeler

PEELER

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
100mm/sec

Print Width
104mm, 832 Dots/line

Resolution
203 dpi (8dots/mm, 0.125 Pitch)

Memory
FLASH : 16MB (Max.32MB)
SDRAM : 16MB(Max.32MB)

Battery Voltage / Capacity
7.4V 3350mAh, 6700mAh
3.5Hrs Charging time(3350mAh)
6.5Hrs Charging time(6700mAh)
118Hrs Stand-by(6700mAh)

Sensor
Paper end, Gap, Black mark,
Cover open, Peeler detect,
Peeler S/W

Reliability
TPH life : 50km

PHYSICAL CHARACTERISTICS

Dimension (W x L x D)
6.5"×6.8"×3.1"
(166 × 174 × 80mm)

Weight
1kg (with 2600mAh battery)

Display
WQVGA Color graphic 3" TFT LCD

INTERFACES

Standard
USB, Serial(RS-232C)

Optional
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE)

ACCESSORIES

Standard
AC Cord, USB Cable, Serial Cable,
Battery Pack, Thermal Roll Paper,
Belt Clip, Power Adaptor

Optional
Shoulder Strap, Vehicle Charger,
Battery Cradle (P43), Peeler, RTC

OPERATING CHARACTERISTICS

Operating Temperature
-21 ~ 55°C

Operating Humidity
10 ~ 90%

Storage Temperature
-30 ~ 65°C

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP54 certified

Drop Rating
1.8m(set only)

BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
UPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39

SOFTWARE

Emulations
ESC/POS, CPCL, ZPL Command
compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS
Driver, iOS SDK, Android(6.0 ~) SDK

MEDIA CHARACTERISTICS

Media Type
Thermal Receipt/Label

Media Width
50~112mm

Media Core Diameter
12.5mm ± 0.5mm

Media Roll Diameter
Max. Ø 56mm

Thickness
0.06 ~ 0.16mm

FONTS / GRAPHICS

Character Type
FontA(12x24), FontB(9x17),
Font0/1/2/4/5/6/7, TTF Font0, FontA~H,
FontGS, Font1~8, Asian Font(KOR, JPN,
CHN_GB2312, CHN_BIG5), Resident TTF,
Downloadable TTF, Downloadable Bitmap

Characters per Line (CPL)
Font A(12x24): 69 columns
Font B(9x17): 92 columns

Character Set
Alpha numeric character : 95
Expanded graphic :
128*18 page(1 space page)
International character : 14

CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, MFI,
UKCA, BCS, CB

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprnter.com

