

sewoo

DIRECT THERMAL POS PRINTER

# SLK-TL212II



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Wall mount installation available



Barcode



Durable

50~82.5MM

Paper  
Width



Paper  
Sensor



Easy  
Loading



Fast  
Speed



Compact  
Design



Easy  
Maintenance



Energy  
Star

## APPLICATION



## SPECIFICATIONS

### **PRINTER CHARACTERISTICS**

**Print Method**  
Direct thermal

**Print Speed**  
Up to 8.6ips(220mm/sec)

**Print Width**  
Up to 2.8"(72mm)

**Resolution**  
180dpi

**Power**  
Power type : External SMPS  
AC : 100~240Vac 50/60Hz  
DC : 24Vdc / 1.75A

**Sensor**  
Standard: Paper End, Paper Low,  
Cover Open  
Option : Black Mark

**Reliability**  
TPH life : 160km  
MCBF : 60 Million lines  
Cutter life : 2.0 Million cuts

**Drawer port**  
2 circuits(24V, 1A Max.)

### **PHYSICAL CHARACTERISTICS**

**Dimension (W x D x H)**  
5.98" x 8.03" x 5.82"  
(152 x 204 x 150mm)

**Weight**  
3.74lb(1.7Kg)

### **INTERFACES**

**Standard**  
USB(B type)+ Serial  
(RS-232C\_9pin) Built-in

### **CERTIFICATIONS**

CE, FCC, KC, UL/cUL,  
ENERGY STAR

### **OPERATING CHARACTERISTICS**

**Operating Temperature**  
32 ~ 113°F(0 ~ 45°C)

**Operating Humidity**  
10 ~ 80RH%

**Storage Temperature**  
-4 ~ 140°F(-20 ~ 60°C)

**Storage Humidity**  
10 ~ 90%

### **MEDIA CHARACTERISTICS**

**Media Type**  
Thermal receipt paper,  
Linerless(Optional)

**Media Width**  
1.9~3.2"(50mm ~82.5mm)

**Media Core Diameter**  
0.4"(12.5mm ± 0.5mm)

**Media Roll Diameter**  
3.1"(ø 80mm)

**Thickness**  
0.06~0.09mm

### **SOFTWARE**

**Emulations**  
ESC/POS Command compatible

**Drivers**  
Windows Driver(XP ~, Server2003 ~),  
Windows CE & Mobile Driver (CE 4.2 ~,  
Mobile 5.0 ~), Linux Driver, Mac Driver,  
OPOS Driver, JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK, Windows SDK,  
Windows CE SDK Linux SDK

### **BARCODES**

**1D**  
EAN-8, EAN-13, Code 39,  
Code 93, Code 128, ITF,  
UPC-A, UPC-E, Codabar

**2D**  
PDF 417, QR code, DATA MATRIX

### **FONTS / GRAPHICS**

**Character Type**  
Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

**Characters per line (CPL)**  
Font A(12x24) : 42cpl,  
Font B(9x17) : 56cpl,

**Character set**  
95 Alphanumeric,  
14 International,  
128 x 18 Graphic

### **ACCESSORIES**

**Standard**  
Power Adaptor 24Vdc / 1.75A

**Option**  
Melody Box

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea  
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA  
T. +1-310-617-7401  
E. NA\_sales@miniprinter.com

México Office

Cuahtémoc, D.F. Mexico. CP 06500  
T. +52-1-55-3232-9543 M. +52-1-55-143893  
E. LA\_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu  
T. +86-177-1729-9100  
E. sales@miniprinter.com

