

sewoo

Board on the economic class being served with a great performance.

# LK-P25II



- Economic but, excellent performance
- Ultra Compact and Lightweight
- Large Battery Capacity
- Wide Compatibility
- USB-C Type Charging Port
- S-MDM (Sewoo MDM) supported



Bluetooth



Barcode



Portable



Durable



Drop Resistant



Easy Loading



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

80mm/sec

#### Print Width

48mm, 384 Dots/line

#### Resolution

203 DPI

#### Memory

8MB(Max 64MB), SRAM 8MB

#### Battery Voltage / Capacity

3.6V 3250mAh Li-ion

4Hrs Charging time(Charger)

6 Hrs Charging time(USB)

#### Standby Time

63 Hrs

#### Sensor

Paper end,  
Cover open(Black mark sensor)

#### Reliability

TPH life : 50km



### PHYSICAL CHARACTERISTICS

#### Dimension (W x L x D)

3.1" × 4.06" × 1.74"  
(79 × 103.2 × 44.4mm)

#### Weight

190g - TBD



### INTERFACES

#### Standard

USB C Type, Bluetooth Smart Ready  
(Bluetooth4.2+BLE+NFC Tag)



### CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, Mfi,  
UKCA, BCS, CB



### OPERATING CHARACTERISTICS

#### Operating Temperature

-10 ~ 50°C

#### Operating Humidity

10 ~ 80%

#### Storage Temperature

-20 ~ 60°C

#### Storage Humidity

10 ~ 90%

#### Drop Rating

1.5m(set only), 1.8m(with case)

#### Dust-and Water-resistance Rating

IP54(with case)



### BARCODES

#### 1D

EAN-8, EAN-8(+2+5), EAN-13,  
EAN-13(+2+5), Codabar, Code11,  
Code39, Code93, Code128, ITF,  
UPC-A(+2+5), UPC-E, UPC-E(+2+5),  
Planet, etc

#### 2D

QR, PDF417, MicroPDF417, Maxicode,  
Datamatrix, Aztec, RSS14, TLC39



### SOFTWARE

#### Emulations

ESC/POS, CPCL, ZPL  
Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),  
Window CE & Mobile Driver & SDK  
(CE 4.2~, Mobile 5.0~), Linux Driver,  
Mac Driver, OPOS Driver, JavaPOS  
Driver, iOS SDK, Android(6.0 ~) SDK



### MEDIA CHARACTERISTICS

#### Media Type

Thermal paper

#### Media Width

58mm

#### Media Core Diameter

12.5mm ± 0.5mm

#### Media Roll Diameter

Max. Ø 40mm

#### Thickness

0.06mm



### FONTS / GRAPHICS

#### Character Type

FontA(12x24), FontB(9x17),  
Font0/1/2/4/5/6/7, TTF Font0, FontA~H,  
FontGS, Font1~8, Asian Font(KOR, JPN,  
CHN\_GB2312, CHN\_BIG5), Resident TTF,  
Downloadable TTF, Downloadable Bitmap

#### Characters per Line (CPL)

Font A(12x24): 32 columns,  
Font B(9x17): 42 columns

#### Character Set

Alpha numeric character: 95  
Expanded graphic:  
128\*18 page(1 space page)  
International character: 14



### ACCESSORIES

#### Standard

Thermal Roll Paper,  
Belt Clip & Battery Cover  
AC/DC Adaptor 5VDC

#### Optional

Carrying Case (with Belt Clip),  
Shoulder Strap, IP54 Case

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_sales@miniprinter.com

#### México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA\_sales@miniprinter.com

#### China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprinter.com

