

sewoo

Reliable Barcode & Tag Printer

LK-B20II



- Fast Print Speed : 127mm/sec
- Excellent Compatibility
- Stable & Reliable label printing
- Thermal transfer and Direct thermal printing
- Easy to use and maintenance
- Support label design software "Label Cooker"
- Option : Peeler, Auto-cutter, External paper supply



WiFi



Bluetooth



Barcode



Durable



Easy
Loading



127
mm/sec

Fast
Speed



Compact
Design



Easy
Replacement



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

127mm/sec

Print Width

104mm (4.1")

Resolution

203 dpi (8dots/mm)

Memory

Main Flash 1MB

SDRAM 16MB

FONT Flash 8MB

Sensor

Gap, Black mark, Cover open,

Ribbon encoder

Power

Type : External SMPS

AC : 100~240Vac, 1.5A, 50~60Hz

DC : 24Vdc 2.5A

Auto-cutter(Optional)

Type : Guillotine

Life : 200,000 Cuts, Max 20 cycle/1 min



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

8.46" x 11.3" x 9.09"
(215 x 287 x 231 mm)

Weight (Kg)

3.6kg



MEDIA CHARACTERISTICS

Media Type

Roll, Fanfold, Tag, Blackmark,
Continuous, Gap, Notch Sensor

Media Width

18 ~118mm

Media Core Diameter

25.4mm (1") or \varnothing 38.1mm(1.5")

Media Roll Diameter

Up to 127mm (5")

Ribbon Width

33~110mm (1.3 ~ 4.3")

Ribbon Length

360M, \varnothing 67mm (2.63")

Thickness

0.065~0.20mm



OPERATING CHARACTERISTICS

Operating Temperature

0 ~ 40°C

Operating Humidity

10 ~ 90%

Storage Temperature

-20 ~ 60°C

Storage Humidity

10 ~ 90%



BARCODES

1D

Code39, Code128 with subsets
A/B/C/Auto, UCC/EAN-128, Code93,
Codabar, Interleaved 2 of 5, UPC-A,
UPC-E, UPC-A and E with 2 or 5 digit
extension, EAN-8, EAN-13, EAN-8 and
13 with 2 or 5 digit extensions,
Postnet, Plessey, MSI-3, German Post
CodeLogmars, Code11,

UPC_Interleaved 2 of 5, Industrial
2 of 5, Standard 2 of 5, Planet, ANSI,
Logmars

2D

MaxiCode, PDF 417, Data Matrix,
QR Code, MicroPDF417, AZTEC,
Code 49, CODABLOCK, RSS



SOFTWARE

Emulations

EPL II, ZPL II Command compatible

Drivers

Windows Driver

Linux Driver

Mac Driver

SDKs

Windows SDK

Android SDK

iOS SDK



INTERFACES

Standard

USB, Serial(RS-232C), Ethernet

Option

Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE)



CERTIFICATIONS

KCC, CE, CB



FONTS / GRAPHICS

EPL II

6 bitmapped

8x12, 10x16, 12x20, 14x24,
32x48, 24x24(KSC5601)

ZPL II

9 bitmapped

5×9, 7×11, 10×18, 10x18, 15×28,
13×26, 40×60, 13x21, 24x24

2 smooth scalable(English, Korean)



ACCESSORIES

Standard

Power Cord, Power Supply,
Interface Cable(USB)

Optional

Peeler, Auto Cutter,
External Paper Supply

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

