

sewoo

Cost-effective and Lightweight Receipt/Label Printer

LK-P41



- Competitive low price
- Excellent Compatibility
- Ultra Compact and Lightweight
- Durable and Resistant to Water and Dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger, Leather Case



WiFi



Bluetooth



Barcode



Portable




Durable



Drop Resistant



Easy Loading



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
80mm/sec

Print Width
104mm, 832 Dots/line

Resolution
203 dpi (8dots/mm, 0.125 Pitch)

Memory
FLASH : 8MB (Max 64MB)
SDRAM : 16MB (Max 64MB)

Battery Voltage / Capacity
7.2V 3350mAh, 6700mAh
4.0Hrs Charging time(3350mAh)
7.5Hrs Charging time(6700mAh)
180Hrs Stand-by(6700mAh)

Sensor
Paper end, Gap,
Black mark, Cover open

Reliability
TPH life : 50km

PHYSICAL CHARACTERISTICS

Dimension (W x L x D)
5.87" × 6.37" × 2.75"
(149 × 162 × 70mm)

Weight
610g (with 3350mAh battery)

INTERFACES

Standar
USB, Serial(RS-232C)

Optional
Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE+NFC Tag)

CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, M,
UKCA, BCS

OPERATING CHARACTERISTICS

Operating Temperature
-10 ~ 50°C

Operating Humidity
35 ~ 80%

Storage Temperature
-20~ 60°C

Storage Humidity
10 ~ 90%

Dust and Water Resistance Rating
IP54(with case) certified

Drop Rating
1.2m(set only), 1.8m(with case)

BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
UPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39

SOFTWARE

Emulations
ESC/POS, CPCL, ZPL Command compatible

Drivers
Windows Driver(XP~, Server2003~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver, JavaPOS
Driver, iOS SDK, Android(6.0~) SDK

MEDIA CHARACTERISTICS

Media Type
Thermal Receipt/Label

Media Width
50~112mm

Media Core Diameter
12.5mm ± 0.5mm

Media Roll Diameter
Max. Ø 56mm

Thickness
0.06 ~ 0.16mm

FONTS / GRAPHICS

Character Size
FontA(12x24), FontB(9x17),
Font0/1/2/4/5/6/7, TTF Font0, FontA~H,
FontGS, Font1~8, Asian Font(KOR, JPN,
CHN_GB2312, CHN_BIG5), Resident TTF,
Downloadable TTF, Downloadable Bitmap

Characters per Line (CPL)
Font A(12x24): 69 columns
Font B(9x17): 92 columns

Character Set
Alpha numeric character : 95
Expanded graphic :
128*18 page(1 space page)
International character : 14

ACCESSORIES

Standard
USB Cable, Serial Cable,
Battery Pack, Thermal Roll Paper,
Battery Charger (8.4V/1A)

Optional
Battery Cradle (P41)

sewoo

Republic of Korea [Head Office / R&D Center]
28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.
Torrance, CA 90502, USA
T. +1-859-992-5936
E. NA_Sales@miniprinter.com

México
Cauhtémoc, Mexico D.F.
T. +52-1-55-143893 M. +52-1-55-3232-9543
E. LA_Sales@miniprinter.com

