

sewoo

DIRECT THERMAL POS PRINTER

# SLK-TE122\_L



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- 2D barcode supported
- Easy troubleshooting of paper jam by separating cutter cover
- Support restick printing



Barcode



Durable



Paper Width



Paper Sensor



Various interface



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Energy Star



Restick

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

Max. 220mm/sec(8.6ips)

Restick : Max. 160mm/sec(6.2ips)

#### Print Width

Max. 72mm(2.8")

#### Resolution

Standard: 180dpi

#### Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

#### Sensor

Standard: Paper End, Paper Low,  
Cover Open

Option : Black Mark

#### Reliability

TPH life : 160km

Restick TPH life : 100km

MCBF : 60 Million lines

Cutter life : 1.8 Million cuts

Restick cutter life : 1 Million cuts

#### Drawer port

2 circuits(24V, 1A Max.)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

152 x 202 x 150.5mm

(5.9" x 7.9" x 5.9")

#### Weight

3.74lb(1.7Kg)



### INTERFACES

#### Standard

USB (B type)

#### Option

Serial(RS-232C), Parallel(IEEE1284),

Ethernet, Wi-Fi(802.11 a/b/g/n),

Bluetooth Ver 2.1(Movon,iOS)

Bluetooth Ver 4.2(Movon,iOS)



### CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR



### OPERATING CHARACTERISTICS

#### Operating Temperature

0 ~ 45°C(32 ~ 113°F)

Restick : 0 ~ 30°C(32 ~ 86°F)

#### Operating Humidity

35 ~ 80%

#### Storage Temperature

-20 ~ 60°C(-4 ~ 140°F)

#### Storage Humidity

10 ~ 90%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper,

Restick(Optional)

#### Media Width

50mm ~82.5mm(1.9~3.2")

#### Media Core Diameter

12.5mm ± 0.5mm(0.4")

#### Media Roll Diameter

ø 80mm(3.1")

#### Thickness

0.06~0.09mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),

Windows CE & Mobile Driver (CE 4.2 ~,

Mobile 5.0 ~), Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK, Windows SDK,

Windows CE SDK, Linux SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

#### 2D

PDF 417, QR code, DATA MATRIX



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

#### Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



### ACCESSORIES

#### Standard

Power Adaptor 24Vdc / 1.75A

#### Option

Melody Box



### COLOR

Cool grey, Ivory

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-859-992-5936

E. NA\_Sales@miniprinter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA\_Sales@miniprinter.com

