

sewoo

Dot impact printer

SLK-D30



- Drop-in paper loading
- 4.7 Lines/sec high speed printing
- Two color printing
- Auto cutter (optional)
- Paper end / Cover open / Paper low sensor
- Black mark sensor (optional)



Barcode



Durable



Paper
width



Paper
Sensor



Easy
Loading



Compact
Design



Easy
Maintenance

APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method

9-pin Serial Dot
Impact Matrix

Print Speed

4.7 Line/sec)

Print Width

Up to 2.5" (63.5mm)

Line Spacing

n/144inch

Data buffer

48 Kbyte

Resolution

160 DPI / 80 DPI

Direction

Bi-Directional (with Logical Seeking)

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 2.5A

Type

Guillotine

Life

1,000,000 cuts

Paper Thickness

0.06 ~ 0.09mm

Cutting Method

Full/Partial Cut

Type

Guillotine

Life

1,000,000 cuts

Paper Thickness

0.06 ~ 0.09mm

Cutting Method

Full/Partial Cut



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

6.14"×9.57"×5.97"
(156x243.2x150mm)

Weight

2.38kg(Cutter),
2.25kg(Non cutter)



INTERFACES

Serial(RS-232C),
Parallel(Centronics 36pin),
Ethernet, USB,
Combo(Serial+USB)



OPERATING CHARACTERISTICS

Operating Temperature

32 ~ 113°F(0 ~ 45°C)

Operating Humidity

35 ~ 80%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Roll paper

Media Width

57.5mm(2.2inch),

69.5mm(2.7inch),

76.2mm(3inch)

Media Copies

Original + 2copies

INK RIBBON

ERC-38 Compatible

(Black, Purple, Black/Red)



SOFTWARE

Emulations

TM-U200, TM-U300, iDP-3540,
SP200 Command Compatible

NO.OF COLUMNS

TM-U200 Emulation : 42/35, 40/33

Other Emulation : 40/33

Drivers

Windows Driver(2012, 8, 7, 2008,

VISTA, 2003, XP, 32bit & 64bit),

Linux Driver, OPOS Driver,

JavaPOS Driver, WEPOS Driverr



CERTIFICATIONS

CE, FCC, KC, UL/cUL



FONTS

Size

7 x 9, 9 x 9 / 5 x 9, 7 x 9



ACCESSORIES

Optional

Melody Box, Spill Proof Cover

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

