

sewoo

It's a totally convenient mobile presented by
Advanced Manual Cutter

LK-P24

LK-P34



- Fast Print Speed : 4 ips
- AMC (Advanced Manual Cutter) supported
- By Pushing a button, Easily paper cut
- Excellent compatibility
- NFC for easy Bluetooth pairing
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Belt Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Drop
Resistant



Easy
Loading



Fast
Speed



Compact
Design



Easy
Maintenance



Improved
Battery Life



S-MDM
Support

LK-P34

FOR 3 INCH



LK-P24

FOR 2 INCH



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

100mm/sec

Print Width

LK-P24 : 48mm

LK-P34 : 72mm

Resolution

203 dpi (8dots/mm)

Memory

LK-P24 : 8MB(Max 64MB),

SDRAM 8MB

LK-P34 : 8MB(Max 64MB),

SDRAM 8MB (MAX.16MB)

Battery Voltage / Capacity

Rechargeable Li-ion battery

LK-P24 : 7.4V / 1,450mAh

LK-P34 : 7.4V / 2,000mAh

Battery Charge time

LK-P24 : Max. 1.7Hrs

LK-P34 : Max. 2.7Hrs

Standby Time

LK-P24 : Max. 36Hrs

LK-P34 : Max. 61Hrs

Sensor

LK-P24 : Paper end, Black mark sensor

LK-P34 : Paper end, Black mark sensor

Reliability

TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

LK-P24 : 3.2"×4.77"×1.78"

(81.5 x 121.4 x 45.3mm)

LK-P34 : 4.23"×5.70"×2.20"

(107.5 x 145 x 56mm)

Weight

LK-P24 : 264.1g (With battery)

LK-P34 : 422g (With battery)



MEDIA CHARACTERISTICS

Media Type

Thermal paper

Media Width

LK-P24 : 58mm

LK-P34 : 80mm

(PAPAER GUIDE: 58mm)

Media Core Diameter

12.5mm ± 0.5mm

Media Roll Diameter

LK-P24 : Max. Ø 40mm

LK-P34 : Max. Ø 50mm

Thickness

0.06mm



OPERATING CHARACTERISTICS

Operating Temperature

-10 ~ 50°C

Operating Humidity

10 ~ 80%

Storage Temperature

-20 ~ 60°C

Storage Humidity

10 ~ 90%

Dust-and Water-resistance Rating

LK-P24 : IP43

LK-P34 : IP54

Drop Rating

1.5m(set only)



BARCODES

1D

EAN-8, EAN-8(+2+5), EAN-13, EAN-13(+2+5), Codabar, Code11, Code39, Code93, Code128, ITF, UPC-A(+2+5), UPC-E, UPC-E(+2+5), Planet, etc

2D

QR, PDF417, MicroPDF417, Maxicode, Datamatrix, Aztec, RSS14, TLC39



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, Mfi, UKCA, BCS



SOFTWARE

Emulations

ESC / POS, CPCL, ZPL Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~), Window CE & Mobile Driver & SDK (CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(6.0 ~) SDK



ACCESSORIES

Standard

LK-P24 : USB cable, Battery pack, Thermal roll paper, Belt strap & Bracket, Battery Charger (8.4V)

LK-P34 : USB Cable, Battery pack, Thermal roll paper, Belt strap, Battery Charger (8.4V)

Option

LK-P24 : Set cradle, Battery cradle, Leather case + Shoulder Strap
LK-P34 : 4bay cradle, Shoulder Strap, Battery cradle (P20), Leather Case



FONTS / GRAPHICS

Character Type

Font A(12×24), Font B(9×17), Asian Font (KOR, JPN, CHN-GB2312, CHN-Big5), Font0/1/2/4/5/6/7, Resident TTF, Downloadable TTF, FontA~H, FontGS, Resident TTF(Font0), Font 1~8

Characters per line (CPL)

LK-P24: Font A(12x24): 32 columns, Font B(9x17): 42 columns,
LK-P34: Font A(12x24): 48 columns, Font B(9x17): 64columns

Character set

Alpha numeric character : 95
Expanded graphic :
128*18 page(1 space page)
International character : 14



INTERFACES

Standard

USB

Optional

Wi-Fi(802.11a/b/g/n),
Bluetooth Smart Ready
(Bluetooth4.2+BLE+NFC Tag)

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprinter.com

