

sewoo

Cost-effective and Light weight receipt printer

LK-P34L



- Fast Print Speed : 100mm/sec
- Excellent Compatibility
- NFC for easy Bluetooth pairing
- Durable and resistant to water and dust
- S-Linerless solution supported
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Belt Strap, Car Charger



WiFi



Bluetooth



Barcode



Portable



Durable



Drop Resistant



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



S-Linerless Solution Support



APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
100mm/sec

Print Width
72mm, 576 Dots/line

Resolution
203 DPI (8dots/mm, 0.125 Pitch)

Memory
8MB(Max 64MB)
SDRAM 8MB (MAX.16MB)

Battery Voltage / Capacity
7.4V / 2,000mAh Li-ion

Battery Charging Time
2.7Hrs

Standby Time
61Hrs

Sensor
Paper end, Black mark sensor

Reliability
TPH life : 50km



PHYSICAL CHARACTERISTICS

Dimension (W x L x D)
4.23" x 5.70" x 2.20"
(107.5 x 145 x 56mm)

Weight
390g(With Battery)



INTERFACES

Standard
USB

Optional
Wi-Fi(802.11a/b/g/n), Bluetooth Smart Ready (Bluetooth4.2+BLE+NFC Tag)



CERTIFICATIONS

KC, CE, FCC, IC, UL/cUL, M, UKCA, BCS, CCC, CB



OPERATING CHARACTERISTICS

Operating Temperature
-10 ~ 50°C

Operating Humidity
10 ~ 80%

Storage Temperature
-20 ~ 60°C

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP54 certified

Drop Rating
1.5m(set only)



BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13, EAN-13(+2+5), Codabar, Code11, Code39, Code93, Code128, ITF, UPC-A(+2+5), UPC-E, UPC-E(+2+5), Planet, etc

2D
QR, PDF417, MicroPDF417, Maxicode, Datamatrix, Aztec, RSS14, TLC39



SOFTWARE

Emulations
ESC/POS, CPCL, ZPL Command compatible

Drivers
Windows Driver(XP ~, Server2003 ~), Window CE & Mobile Driver & SDK (CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(6.0 ~) SDK



MEDIA CHARACTERISTICS

Media Type
Thermal Receipt/Label/ Linerless(Max. Restick)

Media Width
80mm (PAPER GUIDE : 58mm)

Media Core Diameter
12.5mm ± 0.5mm

Media Roll Diameter
Max. Ø 50mm

Thickness
0.06 ~ 0.16mm



FONTS / GRAPHICS

Character Type
FontA(12x24), FontB(9x17), Font0/1/2/4/5/6/7, TTF Font0, FontA~H, FontGS, Font1~8, Asian Font(KOR, JPN, CHN_GB2312, CHN_BIG5), Resident TTF, Downloadable TTF, Downloadable Bitmap

Characters per line (CPL)
Font A(12x24): 48 columns
Font B(9x17): 64 columns

Character set
Alpha numeric character : 95
Expanded graphic :
128*18 page(1 space page)
International character : 14



ACCESSORIES

Standard
USB Cable, Battery pack, Thermal roll paper, Belt strap, Battery Charger (8.4V)

Optional
4Bay Cradle, Battery Cradle (P20), Shoulder Strap, Leather Case

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com

