

sewoo

DIRECT THERMAL POS PRINTER

SLK-TL122



- Energy star qualified for power efficiency
- High speed printing : 220mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- 2D barcode supported
- Easy troubleshooting of paper jam by separating cutter cover



Barcode



Durable

50~82.5MM

Paper width



Paper Sensor



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Energy Star

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

Up to 8.6ips(220mm/sec)

Print Width

Up to 2.8" (72mm)

Resolution

180dpi

Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

Sensor

Standard: Paper End, Paper Low,

Cover Open

Option : Black Mark

Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 2.0 Million cuts

Drawer port

2 circuits(24V, 1A Max.)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

5.98" x 7.95" x 5.91"

(152 x 202 x 150.5mm)

Weight

3.74lb(1.7Kg)



INTERFACES

Standard

USB(B type)+ Serial

(RS-232C_9pin) Built-in



CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR



OPERATING CHARACTERISTICS

Operating Temperature

32 ~ 113°F(0 ~ 45°C)

Operating Humidity

35 ~ 80%

Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Media Width

1.9~3.2"(50mm ~82.5mm)

Media Core Diameter

0.4"(12.5mm ± 0.5mm)

Media Roll Diameter

3.1"(ø 80mm)

Thickness

0.06~0.09mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),

Windows CE & Mobile Driver (CE 4.2 ~,

Mobile 5.0 ~), Linux Driver, Mac Driver,

OPOS Driver, JavaPOS Driver, iOS SDK,

Android(6.0 ~) SDK, Windows SDK,

Windows CE SDK Linux SDK



BARCODES

1D

EAN-8, EAN-13, Code 39,

Code 93, Code 128, ITF,

UPC-A, UPC-E, Codabar

2D

PDF 417, QR code, DATA MATRIX



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

Font A(12x24) : 42cpl,

Font B(9x17) : 56cpl,

Character set

95 Alphanumeric,

14 International,

128 x 18 Graphic



ACCESSORIES

Standard

Power Adaptor 24Vdc / 1.75A

Option

Melody Box

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_sales@miniprnter.com

México Office

Cuahtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA_sales@miniprnter.com

China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

