

sewoo

DIRECT THERMAL POS PRINTER

# SLK-T42



- High speed printing : 200mm/sec
- Paper width adjustable 59mm
- ESC/POS command compatible
- Tear bar type / Auto cutter(Optional)
- Maximize productivity with Compact and Sleek design
- The simplest and efficient design for environments with limited space



Easy Loading



Compact Design




Easy Maintenance



Barcode



Durable



Paper width



Paper Sensor

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

Up to 7.9ips(200mm/sec)

#### Print Width

Up to 2.1"(72mm)

#### Resolution

203dpi

#### Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

#### Sensor

Standard: Paper End, Cover Open

Option : Black Mark

#### Reliability

TPH life : 100km

MCBF : 60 Million lines

Cutter life : 1.0 Million cuts

#### Drawer port

2 circuits(24V, 1A Max.)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

4.7" x 7.16" x 4.17"  
(120 x 182 x 106mm)

#### Weight

1.94lb(0.88Kg)



### INTERFACES

#### Standard

USB(A type)+

Serial(RS-232C\_9pin) Built-in



### CERTIFICATIONS

CE, FCC, KC



### OPERATING CHARACTERISTICS

#### Operating Temperature

32 ~ 113°F(0 ~ 45°C)

#### Operating Humidity

35 ~ 80%

#### Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

#### Storage Humidity

10 ~ 90%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

#### Media Width

2.32"(59mm ± 0.5mm)

#### Media Core Diameter

0.4"(12.5mm ± 0.5mm)

#### Media Roll Diameter

ø 60mm

#### Thickness

0.06~0.09mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),  
Windows CE & Mobile Driver (CE 4.2 ~,  
Mobile 5.0 ~), Linux Driver, Mac Driver,  
OPOS Driver, JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK, Windows SDK,  
Windows CE SDK Linux SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39,  
Code 93, Code 128, ITF, UPC-A,  
UPC-E, Codabar

#### 2D

PDF 417, QR code, DATA MATRIX



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 36cpl,

Font B(9x17) : 48cpl,

#### Character set

95 Alphanumeric,  
14 International,  
128 x 18 Graphic



### ACCESSORIES

#### Standard

Power Adaptor 24Vdc / 1.75A

#### Option

Auto cutter

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_sales@miniprnter.com

#### México Office

Cuahtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA\_sales@miniprnter.com

#### China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprnter.com

