

sewoo

Compact size and Enhanced usability

SLK-CB125



- Compact size cube printer
- Structure for easy maintenance
- Design for enhanced usability
- Convenient jam control structure
- Compact footprint to help easily fit on the counter.
- Supports flexible printing exit way Front exit or top exit.
- Ideal for kitchen/bar printer with melody box(Kitchen buzzer)



WiFi



Bluetooth



Barcode



Paper Width



Easy Loading



Fast Speed



Compact Design



Easy Maintenance



Triple interface

APPLICATION



SPECIFICATIONS



PRINTER CHARACTERISTICS

Print Method

Direct thermal

Print Speed

250mm/sec(9.8ips)

Print Width

80mm(640 Dots/Line)

Resolution

203 DPI

Power

Power type : External SMPS

AC : 110~220Vac 50/60Hz

DC : 24Vdc / 2.5A

Sensor

Paper end, Cover open,

Paper low (only front)

Reliability

TPH life : 150km

MCBF : 80 Million lines

Cutter life : 2.0 Million cuts

Cutter method: Partial / Full cut

Drawer port

2 circuit(24V, Max. 1A)



PHYSICAL CHARACTERISTICS

Dimension (W x D x H)

125×131.5×125mm

(4.92"×5.17"×4.92")

Weight

0.91kg



INTERFACES

Standard

1 : USB(B type)+Serial (RS- 232C_9pin)+Ethernet Built-in

2 : USB(B type)+Serial (RS232C-9Pin)+RJ45(Serial)

Optional

Bluetooth Smart Ready (Bluetooth5.0+BLE) or WiFi(802.11 a/b/g/n) B/T, WF combo



CERTIFICATIONS

KC, CE, FCC, IC, CB, NRTL



OPERATING CHARACTERISTICS

Operating Temperature

0 ~ 45°C

Operating Humidity

10 ~ 80%

Storage Temperature

-10 ~ 60°C

Storage Humidity

10 ~ 90%



MEDIA CHARACTERISTICS

Media Type

Thermal receipt paper

Media Width

58mm / 80mm / 82.5mm

Media Core Diameter

12.5mm ± 0.5mm

Media Roll Diameter

Max. ø 83mm

Thickness

0.06~0.08mm



SOFTWARE

Emulations

ESC/POS Command compatible

Drivers

Windows Driver(XP ~, Server2003 ~),
Linux Driver, Mac Driver, OPOS Driver,
JavaPOS Driver

SDK

Android SDK, iOS SDK, Windows SDK



BARCODES

1D

EAN-8, EAN-13, Code 39, Code 93,
Code 128, ITF, UPC-A, UPC-E, Codabar

2D

PDF 417, QR code



FONTS / GRAPHICS

Character Type

Font A(12x24), Font B(9x17),

Chinese(Traditional/Simplified, 24x24),

Korean(24x24), Japanese(24x24)

Characters per line (CPL)

· 180 DPI

Font A(12x24) : 46/42/30 columns

Font B(9x17) : 62/59/40 columns

· 203 DPI

Font A(12x24) : 53/48/35 columns

Font B(9x17) : 71/64/46 columns

Character set

Alpha Numeric Character : 95

Expand Graphic : 128x18 Page (1 space page)

International Character : 16



ACCESSORIES

Standard

Power Adaptor 24Vdc / 2.5A

Optional

Melody Box, 24V Buzzer, Paper Guide

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprnter.com

www.miniprnter.com

USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA_Sales@miniprnter.com

México

Cuauhtémoc, Mexico D.F.

T. +52-1-55-143893

M. +52-1-55-3232-9543

E. LA_Sales@miniprnter.com

